

Package: SpiGesXML (via r-universe)

October 17, 2024

Type Package

Title Extract data from SpiGes XML files

Version 0.0.6

Maintainer Felix Luginbuhl <felix.luginbuehl@sg.ch>

Description Provide functions to extract data from SpiGes XML files.

License GPL (>= 3)

Encoding UTF-8

LazyData true

Depends R (>= 2.10)

Imports stats, xml2, dplyr, purrr, cli, rlang

RoxygenNote 7.2.3

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

URL <https://swissstatsr.org/SpiGesXML/>

BugReports <https://github.com/swissstatsr/SpiGesXML/issues>

Repository <https://swissstatsr.r-universe.dev>

RemoteUrl <https://github.com/SwissStatsR/SpiGesXML>

RemoteRef HEAD

RemoteSha 5c37ae69b27514005f0c5eaf3a82a3dd0c263fa5

Contents

spiges_get_df	2
spiges_get_name_nodes	2
spiges_get_name_variables	3

Index

4

<code>spiges_get_df</code>	<i>Get SpiGes node as dataframe</i>
----------------------------	-------------------------------------

Description

Return a tibble/dataframe of a SpiGes node name. By default, all variables are returned. Variables can be selected using the ‘variables’ argument.

Usage

```
spiges_get_df(x, node, variables = NULL, schema_xsd = "latest", force = FALSE)
```

Arguments

<code>x</code>	A string, a connection, or a raw vector. See <code>xml2::read_xml</code>
<code>node</code>	Name of the node as string, see <code>get_node_names</code>
<code>variables</code>	Name of the variables, by default returns all variables
<code>schema_xsd</code>	URL of an XSD schema version, by default "latest" version.
<code>force</code>	default FALSE. If TRUE, returns data even if validation error.

Value

`data.frame/tibble`

<code>spiges_get_name_nodes</code>	<i>Get node names available for data extraction of a SpiGes XML</i>
------------------------------------	---

Description

Return main and children node names of an SpiGes XML. The node names "Unternehmen", "Standort", "Fall", "Kantonsdaten" are removed as the function `spiges_get_df()` doesn't provide support to extract their related data.

Usage

```
spiges_get_name_nodes(x)
```

Arguments

<code>x</code>	A string, a connection, or a raw vector. See <code>xml2::read_xml</code>
----------------	--

Value

`vector of node names`

spiges_get_name_variables

List of official variable names by node

Description

Return a list containing the list of the variables names for each SpiGes XML. The names of the list are equivalent of the node names returned by

Usage

`spiges_get_name_variables(schema_xsd)`

Arguments

`schema_xsd` XSD schema file

Details

Source file: <https://www.bfs.admin.ch/bfs/de/home/statistiken/gesundheit/gesundheitswesen/projekt-spiges.assetdetail.28127962.html>

Value

a list of variable names

Index

`spiges_get_df`, 2
`spiges_get_name_nodes`, 2
`spiges_get_name_variables`, 3